

ALLEGATO 2.2

TABELLA CONSUMO CILINDRI PNEUMATICI SERVIZIO ON/OFF

VSTHDP2C		Pressione di lavoro in bar				
			4	5	6	7
DN	Ø	CORSA	Consumo aria in litri per 1 ciclo (A + R)			
100	2 x 125	60	14,292	17,160	20,016	22,872
125	2 x 125	75	17,865	21,450	25,020	28,590
150	2 x 160	85	33,201	39,780	46,410	53,040
200	2 x 200	110	67,760	81,400	94,820	108,240
250	2 x 200	135	83,160	99,900	116,370	132,840
300	2 x 200	160	98,560	118,400	137,920	157,440
350	2 x 250	185	177,896	213,453	249,047	284,641
400	2 x 250	210	201,936	242,298	282,702	323,106
450	2 x 250	235	225,976	271,143	316,357	361,571
500	2 x 320	260	410,602	492,752	574,865	656,968
600	2 x 320	310	489,564	587,512	685,416	783,308
700	2 x 320	360	568,526	682,272	795,967	909,648
800	2 x 400	410	1018,276	1221,997	1425,668	1629,258

ALLEGATO 2.3

TABELLA FORZE CILINDRI PNEUMATICI

		Pressione in kg/cm ²				
Ø cilindro	Spinta Trazione	4	5	6	7	Ø cilindro
125	S	314	392	471	549	125
	T	285	357	428	499	
160	S	314	392	471	549	160
	T	285	357	428	499	
200	S	1256	1570	1884	2198	200
	T	1205	1507	1808	2109	
250	S	1962	2453	2943	3434	250
	T	1884	2355	2826	3297	
320	S	3215	4020	4823	5627	320
	T	2763	3454	4145	4835	
400	S	5024	6280	7536	8792	400
	T	4572	5712	6858	8001	